




Power: 0.6VA
Core: EI30/5
ta 70°C
Weight: 43g
Features

- **Input 2 X 115V 50/60Hz**
- **Safety Isolating transformer**
- **Inherently Short-circuit Proof**
- **130°C Class B Insulation**
- **Two Chambers Winding Design**
- **Dielectric Strength 4,500Vrms**
- **UL 94V0 Material**
- **Vacuum Potting**
- **Customer Design**
- **OEM & Subcontracting**

Part Number	Primary (V)	Secondary (V)	Secondary (mA)	No-Load Voltage (V)	Schematic No.
YZ30XD06-0607B	2X115	2x6	2X50.0	2x10.1	3
YZ30XD06-0907B	2X115	2x9	2X33.3	2x15.6	3
YZ30XD06-1207B	2X115	2x12	2X25.0	2x19.9	3
YZ30XD06-1507B	2X115	2x15	2X20.0	2x23.3	3
YZ30XD06-1807B	2X115	2x18	2X16.7	2x27.9	3
YZ30XD06-2407B	2X115	2x24	2X12.5	2x37.2	3

Packing Information

Model	EI30/5 Series
Carton size LxWxH (mm)	565X195X140
QTY Pcs/carton	300
Weight per carton	13.5kg


Dimensions (in mm)

Front View

Bottom View
Schematics & Pin Connections

Safety Standard

IEC 61558-1
IEC 61558-2-6

UL 1446
UL 5085
UL 506

GB 19212-1
GB 19212-7
