





**Power: 0.5VA**
**Core: EI30/5**
**ta 70°C**
**Weight: 43g**
**Features**

- **Input 230V 50/60Hz**
- **Safety Isolating transformer**
- **Inherently Short-circuit Proof**
- **130°C Class B Insulation**
- **Two Chambers Winding Design**
- **Dielectric Strength 4,500Vrms**
- **UL 94V0 Material**
- **Vacuum Potting**
- **Customer Design**
- **OEM & Subcontracting**

Part Number	Primary (V)	Secondary (V)	Secondary (mA)	No-Load Voltage (V)	Schematic No.
YZ30S05-0607B	230	6	83.3	9.7	1
YZ30S05-0727B	230	7.2	69.4	11.6	1
YZ30S05-0907B	230	9	55.6	14.5	1
YZ30S05-1007B	230	10	50	16.2	1
YZ30S05-1207B	230	12	41.7	19.4	1
YZ30S05-1507B	230	15	33.3	24.3	1
YZ30S05-1807B	230	18	27.8	29.1	1
YZ30S05-2407B	230	24	20.8	38.8	1
YZ30D05-0607B	230	2x6	2x41.7	2x9.7	2
YZ30D05-0727B	230	2x7.2	2x34.7	2x11.7	2
YZ30D05-0907B	230	2x9	2x27.8	2x14.6	2
YZ30D05-1007B	230	2x10	2x25.0	2x16.2	2
YZ30D05-1207B	230	2x12	2x20.8	2x19.4	2
YZ30D05-1507B	230	2x15	2x16.7	2x24.3	2
YZ30D05-1807B	230	2x18	2x13.9	2x29.2	2
YZ30D05-2407B	230	2x24	2x10.4	2x38.9	2

**Packing Information**

Model	EI30/5 Series
Carton size LxWxH (mm)	565X195X140
QTY Pcs/carton	300
Weight per carton	13.5kg


**Dimensions (in mm)**

**Front View**

**Bottom View**
**Schematics & Pin Connections**

**Safety Standard**

**IEC 61558-1**  
**IEC 61558-2-6**

**UL 1446**  
**UL 5085**  
**UL 506**

**GB 19212-1**  
**GB 19212-7**
